



# Abodo Vaaro<sup>®</sup> Fire

Extreme Performance Feature Timber

New Growth Feature Timbers

**ABODO**



# INTRODUCING / Abodo Vaaro® Fire

## A World First Timber Innovation



Abodo Vaaro® Fire is the only fire compliant\*, ultra-durable timber available as a complete coated and tested product range – all from one trusted manufacturer.

**In Europe, Vaaro meets:**

- EN16755:2017, B-s2, d0 / B-s1, d0  
DRF EXT INT1 INT2

<b>Fire Performance</b>	Vaaro has been extensively tested worldwide to major fire standards*, in coated and uncoated forms, before and after weathering
<b>Leach Resistance</b>	Very high leach resistance in exterior applications
<b>Durability</b>	Excellent long term resistance to fungal decay, including a 40 Year Durability Warranty (subject to warranty conditions)
<b>Coatings</b>	Fully tested with Abodo Protector semi-transparent coating range**
<b>Sustainability</b>	Made from high grade Forest Stewardship Council® (FSC®) certified rapidly renewable New Zealand plantation timber
<b>Processing</b>	Can be re-machined after treatment, up to 4mm – subject to conditions***

Suitable for exterior and interior applications

Low-corrosivity to most metals

Increased density and hardness

All from a single manufacturer

Low dimensional movement

Non toxic, no heavy metals, boron or halogens

\* Abodo's Vaaro has been tested to and has achieved AS/NZS 3837:1998 Type A and ISO 9705:2003 Group 1-S (NZ), AS 3959:2018 BAL29 and AS 5637.1:2015 Group 1 (AU), B-s2, d0 (LVG) / B-s1, d0 (Flatsawn) (EN 13501-1:2018) DRF EXT INT1 INT2 (EN 16755:2017) (UK+EU), and ASTM E84 Class A (USA) fire compliance standards.

\*\* Testing may vary across markets.

\*\*\* Maximum 1mm off the face and 3mm of the back with minimum 18mm nominal thickness for a finished board.



[abodowood.com](http://abodowood.com)

See the Vaaro Product Guide for more information.  
Go to [abodowood.com/resources](http://abodowood.com/resources) to download.

FSC® C010962