



Abodo Vaaro® Fire

Extreme Performance Feature Timber

New Growth Feature Timbers

ABODO



INTRODUCING / Abodo Vaaro® Fire

A World First Timber Innovation



Abodo Vaaro® Fire is the only fire compliant*, ultra-durable timber available as a complete coated and tested product range – all from one trusted manufacturer.

In the United Kingdom, Vaaro meets:

- EN16755:2017, B-s2, d0 / B-s1, d0
- DRF EXT INT1 INT2

Fire Performance	Vaaro has been extensively tested worldwide to major fire standards*, in coated and uncoated forms, before and after weathering
Leach Resistance	Very high leach resistance in exterior applications
Durability	Excellent long term resistance to fungal decay, including a 40 Year Durability Warranty (subject to warranty conditions)
Coatings	Fully tested with Abodo Protector semi-transparent coating range**
Sustainability	Made from high grade Forest Stewardship Council® (FSC®) certified rapidly renewable New Zealand plantation timber
Processing	Can be re-machined after treatment, up to 4mm – subject to conditions***

☐ Suitable for exterior and interior applications

☐ Low-corrosivity to most metals

☐ Increased density and hardness

☐ All from a single manufacturer

☐ Low dimensional movement

☐ Non toxic, no heavy metals, boron or halogens

* Abodo's Vaaro has been tested to and has achieved AS/NZS 3837:1998 Type A and ISO 9705:2003 Group 1-S (NZ), AS 3959:2018 BAL29 and AS 5637.1:2015 Group 1 (AU), B-s2, d0 (LVG) / B-s1, d0 (Flatsawn) (EN 13501-1:2018) DRF EXT INT1 INT2 (EN 16755:2017) (UK+EU), and ASTM E84 Class A (USA) fire compliance standards.

** Testing may vary across markets.

*** Maximum 1mm off the face and 3mm of the back with minimum 18mm nominal thickness for a finished board.



abodowood.co.uk

See the Vaaro Product Guide for more information.
Go to abodowood.co.uk/resources to download.

FSC® C010962